

DIRECTIONS: FIRST, read down to find use...THEN, across for REGULATIONS												
Section 60.97	USE REGULATIONS	Required Review Process	MINIMUMS				MAXIMUMS		Landscape Category (See Ch. 95)	Sign Category (See Ch. 100)	Required Parking Spaces (See Ch. 105)	Special Regulations (See also General Regulations)
			Lot Size	REQUIRED YARDS (See Ch. 115)			Lot Coverage	Height of Structure				
				Front	Side	Rear						
.010	Detached Dwelling Unit	None	3,600 sq. ft.	10'	5'	10'	60%	30' above average building elevation.	E	A	2.0 per unit.	1. For this use, only one dwelling unit may be on each lot regardless of lot size. 2. Chapter 115 KZC contains regulations regarding home occupations and other accessory uses, facilities and activities associated with this use.
.020	Detached, Attached, or Stacked Dwelling Units		3,600 sq. ft. with at least 2,400 sq. ft. per unit.	20'	5' for detached units. For attached or stacked units, 5', but 2 side yards must equal at least 15'. See Spec. Reg. 3.	10' See Spec. Reg. 4.			D		1.7 per unit.	1. Chapter 115 KZC contains regulations regarding home occupations and other accessory uses, facilities and activities associated with this use. 2. Chapter 115 KZC contains regulations regarding common recreational space requirements for this use. 3. The side yard may be reduced to zero feet if the side of the dwelling unit is attached to a dwelling unit on an adjoining lot. If one side of a dwelling unit is so attached and the opposite side is not, the side that is not attached must provide a minimum side yard of five feet. 4. The rear yard may be reduced to zero feet if the rear of the dwelling unit is attached to a dwelling unit on an adjoining lot.
.030	Church	Process IIA, Chapter 150 KZC.	7,200 sq. ft.		20' on each side	20'	70%		C	B	1 for every 4 people based on maximum occupancy load of any area of worship. See Spec. Reg. 1.	1. No parking is required for day-care or school ancillary to this use.

DIRECTIONS: FIRST, read down to find use...THEN, across for REGULATIONS												
Section 60.97	USE REGULATIONS	Required Review Process	Lot Size	MINIMUMS			MAXIMUMS		Landscape Category (See Ch. 95)	Sign Category (See Ch. 100)	Required Parking Spaces (See Ch. 105)	Special Regulations (See also General Regulations)
				REQUIRED YARDS (See Ch. 115)			Lot Coverage	Height of Structure				
				Front	Side	Rear						
.040	School or Day-Care Center	Process IIA, Chapter 150 KZC.	7,200 sq. ft.	If this use can accommodate 50 or more students or children, then: 50' 50' on each side 50'			70%	30' above average building elevation. See Spec. Reg. 9.	D	B	See KZC 105.25.	<ol style="list-style-type: none"> 1. May locate on the subject property only if: <ol style="list-style-type: none"> a. It will serve the immediate neighborhood in which it is located; or b. It will not be detrimental to the character of the neighborhood in which it is located. 2. A six-foot-high fence is required only along the property lines adjacent to the outside play areas. 3. Hours of operation may be limited to reduce impacts on nearby residential uses. 4. Structured play areas must be setback from all property lines as follows: <ol style="list-style-type: none"> a. 20 feet if this use can accommodate 50 or more students or children. b. 10 feet if this use can accommodate 13 to 49 students or children. 5. An on-site passenger loading area must be provided. The City shall determine the appropriate size of the loading areas on a case-by-case basis, depending on the number of attendees and the extent of the abutting right-of-way improvements. Carpooling, staggered loading/unloading time, right-of-way improvements or other means may be required to reduce traffic impacts on any nearby residential uses. 6. May include accessory living facilities for staff persons. 7. The location of parking and passenger loading areas shall be designed to reduce impacts on any nearby residential uses. 8. These uses are subject to the requirements established by the Department of Social and Health Services (WAC Title 388). 9. For school use, structure height may be increased, up to 35 feet, if: <ol style="list-style-type: none"> a. The school can accommodate 200 or more students; and b. The required side and rear yards for the portions of the structure exceeding the basic maximum structure height are increased by one foot for each additional one foot of structure height; and c. The increased height is not specifically inconsistent with the applicable neighborhood plan provisions of the Comprehensive Plan. d. The increased height will not result in a structure that is incompatible with surrounding uses or improvements.
				If this use can accommodate 13 to 49 students or children, then: 20' 20' on each side 10'								

DIRECTIONS: FIRST, read down to find use...THEN, across for REGULATIONS

Section 60.97	USE ↓ REGULATIONS ↓	Required Review Process	MINIMUMS			MAXIMUMS		Landscape Category (See Ch. 95)	Sign Category (See Ch. 100)	Required Parking Spaces (See Ch. 105)	Special Regulations (See also General Regulations)	
			Lot Size	REQUIRED YARDS (See Ch. 115)			Lot Coverage					Height of Structure
				Front	Side	Rear						
.050	Mini-School or Mini-Day-Care	None	3,600 sq. ft.	20'	5', but 2 side yards must equal at least 15'.	10'	60%	30' above average building elevation.	E	B	See KZC 105.25.	<ol style="list-style-type: none"> May locate on the subject property only if: <ol style="list-style-type: none"> It will serve the immediate neighborhood in which it is located; or It will not be detrimental to the character of the neighborhood in which it is located. A six-foot-high fence is required only along the property lines adjacent to the outside play area. Hours of operation may be limited by the City to reduce impacts on nearby residential uses. Structured play areas must be setback from all property lines by five feet. An on-site passenger loading area may be required depending on the number of attendees and the extent of the abutting right-of-way improvements. The location of parking and passenger loading areas shall be designed to reduce impacts on any nearby residential uses. May include accessory living facilities for staff persons. These uses are subject to the requirements established by the Department of Social and Health Services (WAC Title 388).
.060	Assisted Living Facility	Process IIA, Chapter 150 KZC.	3,600 sq. ft.						D	A	1.7 per independent unit. 1 per assisted living unit.	<ol style="list-style-type: none"> A facility that provides both independent dwelling units and assisted living units shall be processed as an assisted living facility. If a nursing home use is combined with an assisted living facility use in order to provide a continuum of care for residents, the required review process shall be the least intensive process between the two uses. For density purposes, two assisted living units shall constitute one dwelling unit. Total dwelling units may not exceed the number of stacked dwelling units allowed on the subject property. Through Process IIB, Chapter 152 KZC, up to 1 1/2 times the number of stacked dwelling units allowed on the subject property may be approved if the following criteria are met: <ol style="list-style-type: none"> Project is of superior design, and Project will not create impacts that are substantially different than would be created by a permitted multifamily development. The assisted living facility shall provide usable recreational space of at least 100 square feet per unit, in the aggregate, for both assisted living units and independent dwelling units, with a minimum of 50 square feet of usable recreational space per unit located outside. Chapter 115 KZC contains regulations regarding home occupations and other accessory uses, facilities, and activities associated with this use.

Section 60.97

Zone
PLA6I

USE ZONE CHART

DIRECTIONS: FIRST, read down to find use...THEN, across for REGULATIONS												
Section 60.97	USE ↓ REGULATIONS ↓	Required Review Process	Lot Size	MINIMUMS			MAXIMUMS		Landscape Category (See Ch. 95)	Sign Category (See Ch. 100)	Required Parking Spaces (See Ch. 105)	Special Regulations (See also General Regulations)
				REQUIRED YARDS (See Ch. 115)			Lot Coverage	Height of Structure				
				Front	Side	Rear						
.070	Convalescent Center or Nursing Home	Process IIA, Chapter 150 KZC.	None	20'	10' on each side	10'	70%	30' above average building elevation.	C	B	1 for each bed.	1. If a nursing home use is combined with an assisted living facility use in order to provide a continuum of care for residents, the required review process shall be the least intensive process between the two uses. 1. Landscape Category A or B may be required depending on the type of use on the subject property and the impacts associated with the use on the nearby uses.
.080	Public Utility				20' on each side				A		See KZC 105.25.	
.090	Government Facility or Community Facility				10' on each side				C See Spec. Reg. 1.			
.100	Public Park	Development standards will be determined on a case-by-case basis. See Chapter 49 KZC for required review process.										

This page left intentionally blank.